
FHWA Noise Prediction Model, Off-Site CNEL Interim Conditions

Vista Canyon Ranch
CNEL at Off-Site Noise-Sensitive Land Uses
Interim Existing Conditions

ROADWAY NAME Segment	Number of Lanes in Each Direction	Median Width	ADT Volume	Design Speed (mph)	Distance From Edge of Pavemt	Alpha (1) Factor	Barrier Attn. dB(A)	Vehicle Mix		dB(A) CNEL
								Medium Trucks	Heavy Trucks	
ROADWAY										
Soledad Canyon Rd - West of Golden Valley Rd	3	0	n/a	50	75	0.25	0	1.8%	0.7%	n/a
Soledad Canyon Rd - Between Golden Valley Rd and Whites Canyon Rd	3	0	69,800	50	75	0.25	0	1.8%	0.7%	70.0
Soledad Canyon Rd - Between Whites Canyon Rd and Sierra Hwy	3	0	78,650	50	75	0.25	0	1.8%	0.7%	70.5
Soledad Canyon Rd - Between Sierra Hwy and Vista Canyon Rd	2	0	52,050	50	75	0.25	0	1.8%	0.7%	69.3
Soledad Canyon Rd - Between Vista Canyon Rd and Sand Canyon Rd	2	0	50,950	50	75	0.25	0	1.8%	0.7%	69.2
Soledad Canyon Rd - East of Sand Canyon Rd	2	0	53,400	50	75	0.25	0	1.8%	0.7%	69.4
Lost Canyon Rd - Between Via Princessa and Canyon Park Blvd	2	0	22,100	35	75	0.25	0	1.8%	0.7%	61.6
Lost Canyon Rd - Between Canyon Park Blvd and Jakes Way	2	0	22,100	35	75	0.25	0	1.8%	0.7%	61.6
Lost Canyon Rd - Between La Veda Avenue and Sand Canyon Rd	1	0	9,450	35	75	0.25	0	1.8%	0.7%	58.5
Sand Canyon Rd - Between Sierra Hwy and Soledad Canyon Rd	2	0	18,200	45	75	0.25	0	1.8%	0.7%	63.5
Sand Canyon Rd - Between Soledad Canyon Rd and Lost Canyon Rd	2	0	32,400	45	75	0.25	0	1.8%	0.7%	66.0
Sand Canyon Rd - Between Lost Canyon Rd and Alamo Canyon Dr	1	0	16,625	45	75	0.25	0	1.8%	0.7%	63.7
Sand Canyon Rd - Alamo Canyon Dr and Placerita Canyon Rd	1	0	16,625	45	75	0.25	0	1.8%	0.7%	63.7
Via Princessa - West of Whites Canyon Rd	2	0	n/a	35	75	0.25	0	1.8%	0.7%	n/a
Via Princessa - Between Whites Canyon Rd and Sierra Hwy	2	0	50,900	35	75	0.25	0	1.8%	0.7%	65.2
Via Princessa - Between Sierra Hwy and SR 14	3	0	29,775	35	75	0.25	0	1.8%	0.7%	62.4
Via Princessa - Between SR 14 and Lost Canyon Rd	2	0	6,775	35	75	0.25	0	1.8%	0.7%	56.5
Via Princessa - South of Lost Canyon Rd	2	0	22,100	35	75	0.25	0	1.8%	0.7%	61.6
Sierra Highway - Between Golden Valley Rd and Via Princessa	2	0	54,400	45	75	0.25	0	1.8%	0.7%	68.3
Sierra Highway - Between Via Princessa and Canyon Park Blvd	3	0	54,400	45	75	0.25	0	1.8%	0.7%	67.8
Sierra Highway - Between Canyon Park Blvd and Soledad Canyon Rd	3	0	63,050	45	75	0.25	0	1.8%	0.7%	68.4
Sierra Highway - Between Soledad Canyon Rd and Skyline Ranch Rd	2	0	50,500	45	75	0.25	0	1.8%	0.7%	67.9
Sierra Highway - North of Sand Canyon Rd	1	0	21,200	45	75	0.25	0	1.8%	0.7%	64.8
Skyline Ranch Rd - North of Sierra Hwy	2	0	n/a	35	75	0.25	0	1.8%	0.7%	n/a
Whites Canyon Rd - Between Via Princessa and Soledad Canyon Rd	3	0	33,100	35	75	0.25	0	1.8%	0.7%	62.9
Jakes Way - East of Canyon Park Blvd	1	0	9,150	40	75	0.25	0	1.8%	0.7%	59.8
Golden Valley Rd - South of Newhall Ranch Rd	3	0	n/a	35	75	0.25	0	1.8%	0.7%	n/a
Golden Valley Rd - South of SR 14	2	0	n/a	35	75	0.25	0	1.8%	0.7%	n/a
Placerita Canyon Rd - Between Delden Rd and Ravenhill Rd	1	0	10,500	50	75	0.25	0	1.8%	0.7%	62.9
Placerita Canyon Rd - Ravenhill Rd and Sand Canyon Rd	1	0	10,500	50	75	0.25	0	1.8%	0.7%	62.9
Sandy Dr - Between Sierra Hwy and Jakes Way	1	0	8,150	35	75	0.25	0	1.8%	0.7%	57.9
Canyon Park Blvd - Between Sierra Hwy and SR 14	2	0	12,000	35	75	0.25	0	1.8%	0.7%	59.0
Lost Canyon Rd - Between Jakes Way and Vista Canyon Rd (On-site)	2	0	n/a	35	75	0.25	0	1.8%	0.7%	n/a
Vista Canyon Rd - Between Soledad Canyon Rd and Lost Canyon Rd (On-site)	1	0	n/a	35	75	0.25	0	1.8%	0.7%	n/a

Notes:

(1) Alpha Factor: Coefficient of absorption relating to the effects of the ground surface. An alpha factor of 0 indicates that the site is an acoustically "hard" site, such as asphalt. An alpha factor of 0.5 indicates that the site is an acoustically "soft" site such, as heavily vegetated ground cover.

Assumed 24-Hour Traffic Distribution:

	Day	Evening	Night	Total
Total ADT Volumes	77.70%	12.70%	9.60%	100.00%
Medium-Duty Trucks	87.43%	5.05%	7.52%	100.00%
Heavy-Duty Trucks	89.10%	2.84%	8.06%	100.00%

Vista Canyon Ranch
CNEL at Off-Site Noise-Sensitive Land Uses
Interim Project Conditions

ROADWAY NAME Segment	Number of Lanes in Each Direction	Median Width	ADT Volume	Design Speed (mph)	Distance From Edge of Pavement	Alpha (1) Factor	Barrier Attn. dB(A)	Vehicle Mix		dB(A) CNEL
								Medium Trucks	Heavy Trucks	
ROADWAY										
Soledad Canyon Rd - West of Golden Valley Rd	3	0	n/a	50	75	0.25	0	1.8%	0.7%	n/a
Soledad Canyon Rd - Between Golden Valley Rd and Whites Canyon Rd	3	0	75,600	50	75	0.25	0	1.8%	0.7%	70.4
Soledad Canyon Rd - Between Whites Canyon Rd and Sierra Hwy	3	0	85,280	50	75	0.25	0	1.8%	0.7%	70.9
Soledad Canyon Rd - Between Sierra Hwy and Vista Canyon Rd	2	0	61,995	50	75	0.25	0	1.8%	0.7%	70.0
Soledad Canyon Rd - Between Vista Canyon Rd and Sand Canyon Rd	2	0	56,850	50	75	0.25	0	1.8%	0.7%	69.6
Soledad Canyon Rd - East of Sand Canyon Rd	2	0	58,880	50	75	0.25	0	1.8%	0.7%	69.8
Lost Canyon Rd - Between Via Princessa and Canyon Park Blvd	2	0	20,615	35	75	0.25	0	1.8%	0.7%	61.3
Lost Canyon Rd - Between Canyon Park Blvd and Jakes Way	2	0	20,615	35	75	0.25	0	1.8%	0.7%	61.3
Lost Canyon Rd - Between La Veda Avenue and Sand Canyon Rd	1	0	15,850	35	75	0.25	0	1.8%	0.7%	60.8
Sand Canyon Rd - Between Sierra Hwy and Soledad Canyon Rd	2	0	18,840	45	75	0.25	0	1.8%	0.7%	63.7
Sand Canyon Rd - Between Soledad Canyon Rd and Lost Canyon Rd	2	0	36,615	45	75	0.25	0	1.8%	0.7%	66.5
Sand Canyon Rd - Between Lost Canyon Rd and Alamo Canyon Dr	1	0	17,920	45	75	0.25	0	1.8%	0.7%	64.1
Sand Canyon Rd - Alamo Canyon Dr and Placerita Canyon Rd	1	0	17,920	45	75	0.25	0	1.8%	0.7%	64.1
Via Princessa - West of Whites Canyon Rd	2	0	n/a	35	75	0.25	0	1.8%	0.7%	n/a
Via Princessa - Between Whites Canyon Rd and Sierra Hwy	2	0	54,195	35	75	0.25	0	1.8%	0.7%	65.5
Via Princessa - Between Sierra Hwy and SR 14	3	0	33,410	35	75	0.25	0	1.8%	0.7%	62.9
Via Princessa - Between SR 14 and Lost Canyon Rd	2	0	7,015	35	75	0.25	0	1.8%	0.7%	56.6
Via Princessa - South of Lost Canyon Rd	2	0	35,780	35	75	0.25	0	1.8%	0.7%	63.7
Sierra Highway - Between Golden Valley Rd and Via Princessa	2	0	58,440	45	75	0.25	0	1.8%	0.7%	68.6
Sierra Highway - Between Via Princessa and Canyon Park Blvd	3	0	58,205	45	75	0.25	0	1.8%	0.7%	68.1
Sierra Highway - Between Canyon Park Blvd and Soledad Canyon Rd	3	0	65,670	45	75	0.25	0	1.8%	0.7%	68.6
Sierra Highway - Between Soledad Canyon Rd and Skyline Ranch Rd	2	0	53,110	45	75	0.25	0	1.8%	0.7%	68.2
Sierra Highway - North of Sand Canyon Rd	1	0	22,050	45	75	0.25	0	1.8%	0.7%	65.0
Skyline Ranch Rd - North of Sierra Hwy	2	0	n/a	35	75	0.25	0	1.8%	0.7%	n/a
Whites Canyon Rd - Between Via Princessa and Soledad Canyon Rd	3	0	34,650	35	75	0.25	0	1.8%	0.7%	63.1
Jakes Way - East of Canyon Park Blvd	1	0	10,020	40	75	0.25	0	1.8%	0.7%	60.2
Golden Valley Rd - South of Newhall Ranch Rd	3	0	n/a	35	75	0.25	0	1.8%	0.7%	n/a
Golden Valley Rd - South of SR 14	2	0	n/a	35	75	0.25	0	1.8%	0.7%	n/a
Placerita Canyon Rd - Between Delden Rd and Ravenhill Rd	1	0	11,080	50	75	0.25	0	1.8%	0.7%	63.2
Placerita Canyon Rd - Ravenhill Rd and Sand Canyon Rd	1	0	11,080	50	75	0.25	0	1.8%	0.7%	63.2
Sandy Dr - Between Sierra Hwy and Jakes Way	1	0	9,430	35	75	0.25	0	1.8%	0.7%	58.5
Canyon Park Blvd - Between Sierra Hwy and SR 14	2	0	12,000	35	75	0.25	0	1.8%	0.7%	59.0
Lost Canyon Rd - Between Jakes Way and Vista Canyon Rd (On-site)	2	0	12,000	35	75	0.25	0	1.8%	0.7%	59.0
Vista Canyon Rd - Between Soledad Canyon Rd and Lost Canyon Rd (On-site)	1	0	9,200	35	75	0.25	0	1.8%	0.7%	58.4

Notes:

(1) Alpha Factor: Coefficient of absorption relating to the effects of the ground surface. An alpha factor of 0 indicates that the site is an acoustically "hard" site, such as asphalt. An alpha factor of 0.5 indicates that the site is an acoustically "soft" site such, as heavily vegetated ground cover.

Assumed 24-Hour Traffic Distribution:

	Day	Evening	Night	Total
Total ADT Volumes	77.70%	12.70%	9.60%	100.00%
Medium-Duty Trucks	87.43%	5.05%	7.52%	100.00%
Heavy-Duty Trucks	89.10%	2.84%	8.06%	100.00%